



commercial sectional doors



TriCore STANDARD, white, with full-view windows



AlumaView STANDARD, bronze-anodized



SteelForm STANDARD, white, with oval windows

TRICORE™
SECTIONAL THERMAL DOORS

THERMASEAL™
SECTIONAL THERMAL DOORS

STEELFORM™
SECTIONAL RIBBED DOORS

ALUMAVIEW™
SECTIONAL RAIL & STILE DOORS

STYLEFORM™
SECTIONAL RAISED PANEL DOORS

OVER HALF A CENTURY OF WORKING WITH ARCHITECTS AND SPECIFIERS

Professionals like you have counted on Raynor commercial doors and operators for over 50 years. We pride ourselves on fast, individualized product information and service, and we can provide product information via fax or next-day delivery. For your convenience, our commercial specifications and drawings can be downloaded from our website and are available on CD-ROM. Raynor Field Representatives are also available to assist with product specifications as well as provide technical training. Our exclusive, professional network of over 600 dealers and their commitment to customer service has helped make us recognized experts in the industry for over 50 years. Count on your Raynor Dealer for the proper selection and expert installation you deserve.

NEW! Every Raynor Commercial Sectional door is available with our optional white, powder-coated hardware system.



TRICORE™
SECTIONAL THERMAL DOORS

With a proven track record for thermal efficiency and extreme durability, 3"-thick TriCore is simply the best commercial sectional door you can specify. With expanded polystyrene insulation bonded between two steel skins, TriCore has an exceptional R-value of 16.05. When you want the best, specify TriCore.

| Series MODEL | Max. Opening Width | Max. Opening Height | Construction | Surface Texture | Section Thickness | Exterior/Interior Steel Thickness | End Stile Steel Thickness | Insulation (R-Value) | Thermal Break | Exterior Colors | Section Warranty |
|------------------------|--------------------|---------------------|----------------|-----------------|-------------------|--|---------------------------|----------------------|---------------|---|---|
| TriCore OPTIMA (TC-20) | 32' | 24' | Steel Sandwich | Smooth | 3" | 20-Gauge 25-Gauge (Optional 20-Gauge Interior) | 14-Gauge | Polystyrene (16.05) | Yes | White | 1-Year (Rust) 10-Year (Delamination) |
| TriCore STANDARD (TC) | 32' | 24' | Steel Sandwich | Stucco | 3" | 25-Gauge 25-Gauge | 14-Gauge | Polystyrene (16.05) | Yes | White, Frost White*, Dark Brown*, Sepia*, Beige* | 1-Year (Rust) 10-Year (Delamination) |

WARRANTY TriCore door sections carry an exclusive 10-year delamination warranty (of the steel door skins from the insulation) and a 20-year insulation warranty in addition to the standard 1-year limited warranty against any rust on all other door components. See your local Raynor Dealer for complete details.



THERMASEAL™
SECTIONAL THERMAL DOORS

ThermaSeal doors are both durable and energy efficient. An exclusive process fills 100% of the door's interior with energy-saving polyurethane insulation to deliver exceptional R-values of 16.4 for the 1-3/4"-thick model and 14.5 for the 1-1/2" door.

| Series MODEL | Max. Opening Width | Max. Opening Height | Construction | Surface Texture | Section Thickness | Exterior/Interior Steel Thickness | End Stile Steel Thickness | Insulation (R-Value) | Thermal Break | Exterior Colors | Section Warranty |
|---------------------|--------------------|---------------------|----------------|-----------------|-------------------|-----------------------------------|---------------------------|--------------------------|---------------|-----------------------|---|
| ThermaSeal STANDARD | 28' | 20' | Steel Sandwich | Stucco | 1 3/4" | 25-Gauge 26-Gauge | 16-Gauge | Polyurethane Foam (16.4) | Yes | White, Dark Brown* | 1-Year (Rust) 10-Year (Delamination) |
| ThermaSeal BASIC | 16' | 16' | Steel Sandwich | Stucco | 1 1/2" | 26-Gauge 26-Gauge | 16-Gauge | Polyurethane Foam (14.5) | Yes | White | 1-Year (Rust) 10-Year (Delamination) |

WARRANTY ThermaSeal door sections carry a 1-year limited warranty against any rust and a 10-year limited warranty against delamination (of the steel door skins from the insulating foam). Hardware and springs are warranted for 1-year against defects in materials and workmanship. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading



STEELFORM™

SECTIONAL RIBBED DOORS



Rugged SteelForm doors are a standard choice for commercial and industrial garage door needs. Constructed from a single layer of steel with optional windows and insulation, SteelForm sections are a full 2" thick and made of hot-dipped, galvanized steel for maximum rust resistance.

| Series MODEL | Exterior Steel Thickness | Max. Opening Width | Max. Opening Height | Construction | Surface Texture | Section Thickness | End/Center Stile Steel Thickness | Optional Insulation (R-Value) | Exterior Colors | Section Warranty |
|---------------------------------|--------------------------|--------------------|---------------------|--------------|-----------------|-------------------|----------------------------------|--------------------------------------|---|------------------|
| SteelForm OPTIMA (S-16) | 16-Gauge | 24' | 24' | Steel Pan | Smooth (Flush) | 2" | 13-Gauge/16-Gauge | Polystyrene (7.70) Fiberglass (7.57) | White | 1-Year (Rust) |
| SteelForm STANDARD (S-20, S-24) | 20-Gauge | 32' | 24' | Steel Pan | Smooth (Ribbed) | 2" | 16 or 13-Gauge/16-Gauge | Polystyrene (7.70) Fiberglass (7.57) | White Frost White*, Dark Brown*, Sepia*, Beige* | 1-Year (Rust) |
| | 24-Gauge | 24' | 24' | | | | | | | |
| SteelForm BASIC (S-24C) | 24-Gauge Nominal | 16' | 16' | Steel Pan | Smooth (Ribbed) | 2" | 16-Gauge/16-Gauge | Polystyrene (7.70) Fiberglass (7.57) | White | 1-Year (Rust) |

WARRANTY SteelForm doors carry a 1-year limited warranty against any rust. See your local Raynor Dealer for complete details.



ALUMAVIEW™

SECTIONAL RAIL & STILE DOORS

AlumaView has long been the standard fixture for facilities that require a dependable, attractive door with maximum visibility. With an anodized finish in an extruded aluminum frame, AlumaView is available in either 1-3/4" or 2" thick sections. AlumaView is also available in any of 187 ArmorBrite™ powder-coated colors or in special anodized finishes.

| Series MODEL | Max. Opening Width | Max. Opening Height | Overall Section Thickness | End Stile Width | Center Stile Width | Colors | Warranty |
|------------------------|--------------------|---------------------|---------------------------|------------------|--------------------|---|----------|
| AlumaView OPTIMA (HL) | 24' | 24' | 2" | 3 1/4" or 6 1/4" | 3 5/8" | Clear-Anodized Finish or 187 ArmorBrite™ Colors | 1-Year |
| AlumaView STANDARD (L) | 14' | 14' | 1 3/4" | 2 5/8" | 7/16" | Clear-Anodized Finish or 187 ArmorBrite™ Colors | 1-Year |

WARRANTY AlumaView doors carry a 1-year limited warranty. See your local Raynor Dealer for complete details.



STYLEFORM™


SECTIONAL RAISED PANEL DOORS

When exterior appearance is a primary consideration, choose a classic, raised panel door from our attractive StyleForm series.

| Series MODEL | Max. Opening Width | Max. Opening Height | Construction | Surface Texture | Section Thickness | End/Center Stile Steel Thickness | Insulation (R-Value) | Thermal Break | Exterior Colors | Section Warranty |
|---|--------------------|---------------------|----------------------|---------------------------------|-------------------|----------------------------------|----------------------------|---------------|--|-------------------------------------|
| StyleForm OPTIMA (Commercial Decade ShowCase) | 18' | 14' | Steel Sandwich | Raised-Panel/ Flush (Woodgrain) | 2" | 18-Gauge/ N/A | Polystyrene (10.25) | Yes | White, Almond, ClayTone, Brown, Frost White*, Beige*, Sepia*, BronzeTone | 1-Year (Rust) 5-Year (Delamination) |
| StyleForm STANDARD (Commercial Decade II) | 18' | 14' | Steel Pan (24-Gauge) | Raised-Panel (Woodgrain) | 2" | 18-Gauge/ 18-Gauge | Polystyrene-Optional (5.0) | No | White, Almond, ClayTone, Brown, BronzeTone | 1-Year (Rust) |
| StyleForm BASIC (Commercial Classic) | 14' | 14' | Steel Pan | Raised-Panel (Pebblegrain) | 2" | 18-Gauge/ 18-Gauge | Polystyrene-Optional (5.0) | No | White, Almond, ClayTone, Brown | 1-Year (Rust) |

WARRANTY StyleForm door sections carry a 1-year limited warranty against any rust and a 5-year limited warranty against delamination of the steel door skins from the insulating foam. See your local Raynor Dealer for complete details.

*Features the Kynar™ paint process, which provides extended UV protection against fading



POWERHOIST™

COMMERCIAL OPERATORS

Raynor offers a full line of rugged PowerHoist operators for both trolley and jackshaft operation.

| Series MODEL | Operation Mode | Duty Cycle | Drive | Environmental Options (NEMA) | Motor | Logic | Power | Brake | Hand Chain (Jackshaft Only) | Warranty |
|---------------------|----------------------|------------|------------|--|--|----------------------|--|---|-----------------------------|------------------------------------|
| PowerHoist OPTIMA | Jackshaft or Trolley | 30/hr | Gear | 1-Standard 4-Water 7-Explosion 9-Explosion 12-Dust | Continuous-Duty 1/2-2hp O.D.P.-Standard T.E.F.C.-Optional | Relay | 115/230v, 1-Phase 230/460v, 3-Phase | Jackshaft-Standard Trolley-Standard | Standard | 1-Year |
| PowerHoist STANDARD | Jackshaft or Trolley | 30/hr | Belt | 1-Standard 12-Dust | Continuous-Duty 1/3-3/4hp O.D.P.-Standard T.E.F.C.-Optional | Relay | 115/230v, 1-Phase 230/460v, 3-Phase | Jackshaft-Standard Trolley-Optional* | Optional | 1-Year |
| PowerHoist BASIC | Jackshaft or Trolley | 10/hr | Belt | 1-Standard | Intermittent-Duty 1/2hp | Solid State or Relay | 115v, 1-Phase | Jackshaft-Standard Trolley-Optional | Optional | 1-Year Solid State 2-Year Relay |
| PowerHoist SELECT | Trolley | 10/hr | Gear/Chain | 1-Standard | Intermittent-Duty 1/2hp | Solid State | 115v, 1-Phase | Gear Reduction | None | 1-Year |

*Standard on 3/4hp



Need AIA credits? Raynor provides courses covering a variety of door subjects. Call 1-800-4-RAYNOR for more information.

Raynor also offers a complete line of commercial rolling and fire doors, as well as traffic doors.

CALL
1-800-4-RAYNOR

CLICK
www.raynor.com

FAX
1-815-288-7142



Raynor Worldwide P.O. Box 448, 1101 East River Road, Dixon, IL 61021



This information was as complete and factual as possible at the time it was printed. We do, however, reserve the right to make changes in product specifications and availability without notice. Features and options may be different in countries other than the United States. Product colors have been reproduced as well as possible with present commercial printing processes. For absolute accuracy in color matching, use actual product samples.